
Pan Oston®


SLIM SCOCURVED STANDARD



SLIM SCO CURVED STANDARD

Dimensions





Pan Oston B.V.

Adress Hertzstraat 1

8102 PK Raalte The Netherlands

P.O. Box P.O. Box 222

8100 AE Raalte The Netherlands

Phone +31572357755
Email info@panoston.nl
Website panoston.nl

Product options

Туре	Specification
Orientation	Left Right
Scanner placement	Inside core unit Externally mounted
Lane light + number	Optional - Attached to powerpole: White LED colour + number Multi-LED colour + number Multi-LED colour + number + USB camera
LED Lighting	In Core Unit: Single colour (R/G/B) – with physical switch Dual colour (R/G/B) – with physical switch Single colour (RGB) – with PO Smart Controller Multi-colour (RGB) – with PO Smart Controller
Mounting	Fixed to floor – plugs & bolts Fixed to floor – chemical anchoring
Impulse shelves	Optional - Attached to Core Unit
Scanner return point	Optional - Attached to Core Unit
Power / UTP supply	From floor From rear From ceiling - additional power pole is supplied
Weight excl. HW*	65.8 kg

 $^{{}^*} Indicative \ weight \ only. \ Exact \ figure \ depending \ on \ configuration \ and \ accessories$

Hardware preparation (not incl.):

Туре	Specification
Screen	Vesa 75 Vesa 100 ELO 1-Serie 22inch ELO 1739L Ilyama 72336 Iiyama 1732 Ilyama TF1534 Toshiba 6149 - FEC AM1017 Anytouch WTM215TL Others on request
Scanner	Vertical plane scanner: Datalogic Magellan 3450VSi Datalogic Magellan 3200VSi Zebra DS7708 Others on request
Printer	Epson TM-T88 Others on request
PC	Max. dimensions: 450 x 460 x 500mm
EFT	Verifone P400 Verifone VX820 IPP 320-350 Worldline Yomani Others on request